Do not check a source reference to the Test... Frame
effective: True

$$\left\{ \texttt{isPrefixOfS} \left(\begin{array}{l} \mathsf{Test}, \\ \texttt{case listToMaybe} \left(\texttt{getFrameByID} \left(\begin{array}{l} \texttt{fnDB}, \\ \texttt{source} \left(rel \right) \end{array} \right) \right) \texttt{ of} \\ \quad \texttt{Just} \rightarrow \texttt{name} \\ \quad \texttt{Nothing} \rightarrow \texttt{nilS} \end{array} \right) \right\}$$

Do not check a target reference to the Test... Frame
effective: True

$$\left\{ \texttt{isPrefixOfS} \left(\begin{array}{l} \mathsf{Test}, \\ \texttt{case listToMaybe} \left(\texttt{getFrameByID} \left(\begin{array}{l} \texttt{fnDB}, \\ \texttt{target} \left(rel \right) \end{array} \right) \right) \texttt{ of} \\ \quad \texttt{Just} \rightarrow \texttt{name} \\ \quad \texttt{Nothing} \rightarrow \texttt{nilS} \end{array} \right) \right\}$$

Do not check a source reference to the Boulder Frame
effective: True

$$\left\{ \begin{array}{l} \mathsf{Boulder} = \\ \texttt{case listToMaybe} \left(\texttt{getFrameByID} \left(\begin{array}{l} \texttt{fnDB}, \\ \texttt{source} \left(rel \right) \end{array} \right) \right) \texttt{ of} \\ \quad \texttt{Just} \rightarrow \texttt{name} \\ \quad \texttt{Nothing} \rightarrow \texttt{nilS} \end{array} \right\}$$

Do not check a target reference to the Boulder Frame
effective: True

$$\left\{ \begin{array}{l} \mathsf{Boulder} = \\ \texttt{case listToMaybe} \left(\texttt{getFrameByID} \left(\begin{array}{l} \texttt{fnDB}, \\ \texttt{target} \left(rel \right) \end{array} \right) \right) \texttt{ of} \\ \quad \texttt{Just} \rightarrow \texttt{name} \\ \quad \texttt{Nothing} \rightarrow \texttt{nilS} \end{array} \right\}$$